SAFETY DATA SHEET

1. Identification

Product number 0036

Product identifier Camie 365 Hibond Adhesive LT

Revision date 05-12-2014

Company information Camie-Campbell, Inc.

1005 S. Westgate Drive

Addison, IL 60101 United States

www.camie.com

Company phone General Assistance 1-800-325-9572

Emergency telephone US 1-866-836-8855 **Emergency telephone outside**

US

1-952-852-4646

Version # 03

Supersedes date 04-25-2014 Recommended use Adhesive Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Skin corrosion/irritation **Health hazards** Category 2 Serious eye damage/eye irritation Category 2A

Reproductive toxicity (fertility) Category 2 Category 3 narcotic effects

Specific target organ toxicity, single exposure

Specific target organ toxicity, repeated Category 2

exposure

OSHA defined hazards Not classified.

I abel elements



Signal word Danger

Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. May cause **Hazard statement**

drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through

prolonged or repeated exposure.

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label).

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

Hazardous to the aquatic environment, acute **Environmental hazards** Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Product name: Camie 365 Hibond Adhesive LT

Supplemental information

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Prevention Avoid release to the environment.

44.02% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 35.65% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Hazardous components

Chemical name	Common name and synonyms	CAS number	%
Dimethyl Ether		115-10-6	20 - 40
Acetone		67-64-1	10 - 20
n-Hexane		110-54-3	10 - 20
Propane		74-98-6	10 - 20
2-Methylpentane		107-83-5	2.5 - 10
3-Methylpentane		96-14-0	1 - 2.5
Other components below reportable lev	els		20 - 40

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contactTake off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists. Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Causes s

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Water fog. Dry chemical powder. Alcohol resistant foam. Carbon dioxide (CO2).

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the MSDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

Product name: Camie 365 Hibond Adhesive LT

Product #: 11500011F, 0036, FPAILOVEADH Version #: 03 Revision date: 05-12-2014 Issue date: 03-17-2014

7. Handling and storage

Precautions for safe handling

Do not handle or store near an open flame, heat or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not spray on a naked flame or any other incandescent material. Use only in well-ventilated areas. Provide adequate ventilation. Avoid breathing

dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective.

Do not re-use empty containers. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the MSDS). Level 3 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type `	, Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm	
,	TWA	500 ppm	
3-Methylpentane (CAS 96-14-0)	STEL	1000 ppm	
	TWA	500 ppm	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
,		250 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
,		50 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
US. AIHA Workplace Environmen	tal Exposure Level (WEEL) Gu	ides	
Components	Туре	Value	
Dimethyl Ether (CAS 115-10-6)	TWA	1880 mg/m3	
·		1000 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

Product name: Camie 365 Hibond Adhesive LT

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

ColorNot available.FormAerosol.Physical stateGas.

Flash point -156.00 °F (-104.44 °C) estimated

Melting point/freezing pointNot available.OdorNot available.pHNot available.Solubility(ies)Not available.Vapor densityNot available.

Vapor pressure 47.1 psig @70F estimated

Viscosity Not available.

Other information

Specific gravity 0.782 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardousHazardous polymerization does not occur.

reactions

Conditions to avoidAvoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in

lung edema or pneumonia. However, ingestion is not likely to be a primary route of occupational

exposure.

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause central nervous system effects. Symptoms

of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product name: Camie 365 Hibond Adhesive LT

SDS US

Product Test Results Species Camie 365 Hibond Adhesive LT (CAS Mixture) **Acute** Dermal LD50 Rabbit 104.4386 ml/kg, estimated Rat 18075.8809 mg/kg, estimated Inhalation LC50 Mouse 2349.6196 mg/l, 15 Minutes, estimated 1834.3156 mg/l, 30 Minutes, estimated Rat 10432.7334 mg/l, 15 Minutes, estimated 1466.2548 mg/l, 4 Hours, estimated 1119.4457 mg/l/4h, estimated 261.6188 mg/l, 8 Hours, estimated Oral LD50 Mouse 15665.7959 mg/kg, estimated Rabbit 27885.1172 mg/kg, estimated 174.1027 mg/kg, estimated Rat Other LD50 Mouse 6772.8462 mg/kg, estimated Rat 28720.627 mg/kg, estimated Components **Species Test Results** Acetone (CAS 67-64-1) Acute Dermal LD50 Rabbit 20000 mg/kg 20 ml/kg Inhalation LC50 Rat 76 mg/l, 4 Hours 50.1 mg/l, 8 Hours Oral LD50 3000 mg/kg Mouse Rabbit 5340 mg/kg Rat 5800 mg/kg Other LD50 Mouse 1297 mg/kg Rat 5500 mg/kg Dimethyl Ether (CAS 115-10-6) Acute Inhalation LC50 Mouse 494.36 mg/l, 15 Minutes 385.94 mg/l, 30 Minutes Rat 308.5 mg/l, 4 Hours n-Hexane (CAS 110-54-3) **Acute** Inhalation LC50 Mouse 48000 mg/l, 4 Hours Oral LD50 Rat 24 mg/kg Wistar rat 49 mg/kg Propane (CAS 74-98-6) **Acute** Inhalation LC50 Rat > 1442.847 mg/l, 15 Minutes

Components **Species Test Results**

658 mg/l/4h

Skin corrosion/irritation

Causes skin irritation. Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product		Species	Test Results	
Camie 365 Hibond Adhesive LT (CAS Mixture)				
Crustacea	EC50	Daphnia	678.6467 mg/L, 48 Hours, estimated	
Fish	LC50	Fish	16.1188 mg/L, 96 Hours, estimated	
Components		Species	Test Results	
Acetone (CAS 67-64-	1)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Dimethyl Ether 0.1 -0.24Acetone Propane 2.36 3-Methylpentane 3.6 2-Methylpentane 3.74 n-Hexane 3.9

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable Transport hazard class(es) 2.1

Not available. Subsidiary class(es) Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Labels required Special provisions N82 306 **Packaging exceptions** None Packaging non bulk Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN1950 **UN** number

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1 Subsidiary class(es)

Packaging group Not available.

Nο **Environmental hazards** Labels required 2.1 **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

IMDG

UN1950 **UN** number **UN proper shipping name AEROSOLS**

Transport hazard class(es) Subsidiary class(es)

Packaging group Not available.

Environmental hazards

Marine pollutant No None Labels required

Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) LISTED n-Hexane (CAS 110-54-3) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely

SARA 311/312 Hazardous

No

hazardous substance

Nο

chemical

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Dimethyl Ether (CAS 115-10-6) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Food and Drug Not regulated.

Administration (FDA)

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Dimethyl Ether (CAS 115-10-6) 500 lbs n-Hexane (CAS 110-54-3) 500 lbs Propane (CAS 74-98-6) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

2-Methylpentane (CAS 107-83-5) 3-Methylpentane (CAS 96-14-0) Acetone (CAS 67-64-1) Dimethyl Ether (CAS 115-10-6) n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

Korea Existing Chemicals List (ECL)

New Zealand Inventory New Zealand No **Philippines** Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

03-17-2014 **Revision date** 05-12-2014

Version # 03

Further information Not available.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with

any other materials or in any process, unless specified in the text.

Product and Company Identification: Product Codes **Revision Information**

Composition / Information on Ingredients: Ingredients

Product name: Camie 365 Hibond Adhesive LT

No