

SAFETY DATA SHEET

1. Identification

Product number	0036
Product identifier	Camie 365 Hibond Adhesive LT
Revision date	05-12-2014
Company information	Camie-Campbell, Inc. 1005 S. Westgate Drive Addison, IL 60101 United States www.camie.com
Company phone	General Assistance 1-800-325-9572
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	03
Supersedes date	04-25-2014
Recommended use	Adhesive
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
OSHA defined hazards	Not classified.	

Label elements



Danger
Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Not classified.
Hazardous to the aquatic environment, acute Category 3 hazard
Hazardous to the aquatic environment, Category 3 long-term hazard

Supplemental information

Hazard statement Prevention

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. Avoid release to the environment.

44.02% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 35.65% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Hazardous components			
Chemical name	Common name and synonyms	CAS number	%
Dimethyl Ether		115-10-6	20 - 40
Acetone		67-64-1	10 - 20
n-Hexane		110-54-3	10 - 20
Propane		74-98-6	10 - 20
2-Methylpentane		107-83-5	2.5 - 10
3-Methylpentane		96-14-0	1 - 2.5
Other components below reportable	e levels		20 - 40

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. Wash clothing separately before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing modia	Water for Dry chamical powder, Alcohol resistant form, Carbon diavide (CO2)

Suitable extinguishing media Water fog. Dry chemical powder. Alcohol resistant foam. Carbon dioxide (CO2). Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media Specific hazards arising from Contents under pressure. Pressurized container may explode when exposed to heat or flame. the chemical During fire, gases hazardous to health may be formed. Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire. and precautions for firefighters **Fire-fighting** Move containers from fire area if you can do so without risk. Containers should be cooled with equipment/instructions water to prevent vapor pressure build up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the MSDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

7. Handling and storage

Precautions for safe handling	Do not handle or store near an open flame, heat or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not spray on a naked flame or any other incandescent material. Use only in well-ventilated areas. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not re-use empty containers. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the MSDS). Level 3 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components		Туре			Value	
Acetone (CAS 67-64-1)		PEL			2400 mg/m3	
. ,					1000 ppm	
n-Hexane (CAS 110-54-3)		PEL			1800 mg/m3	
,					500 ppm	
Propane (CAS 74-98-6)		PEL			1800 mg/m3	
, , , , , , , , , , , , , , , , , , ,					1000 ppm	
US. ACGIH Threshold Lim Components	nit Values	Туре			Value	
2-Methylpentane (CAS		STEL			1000 ppm	
107-83-5)						
		TWA			500 ppm	
3-Methylpentane (CAS 96-14-0)		STEL			1000 ppm	
		TWA			500 ppm	
Acetone (CAS 67-64-1)		STEL			750 ppm	
		TWA			500 ppm	
n-Hexane (CAS 110-54-3)		TWA			50 ppm	
US. NIOSH: Pocket Guide	to Chemical Ha	azards				
Components		Туре			Value	
Acetone (CAS 67-64-1)		TWA			590 mg/m3	
					250 ppm	
n-Hexane (CAS 110-54-3)		TWA			180 mg/m3	
					50 ppm	
Propane (CAS 74-98-6)		TWA			1800 mg/m3	
					1000 ppm	
US. AIHA Workplace Envi Components	ronmental Expo	osure Le Type	evel (WEEL) Gu	lides	Value	
Dimethyl Ether (CAS 115-10-6)		TWA			1880 mg/m3	
115-10-0)					1000 ppm	
ogical limit values						
ACGIH Biological Exposu	ire Indices					
Components	Value		Determinant	Specimer	n Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l		Acetone	Urine	*	
n-Hexane (CAS 110-54-3)	0.4 mg/l		2,5-Hexanedio n, without hydrolysis	o Urine	*	
* - For sampling details, ple	ase see the sour	rce docu				
osure guidelines						
US - California OELs: Ski	n designation					
	-		Can	be absorbed th	rough the skin.	
n-Hexane (CAS 110-54	4-3)					
n-Hexane (CAS 110-54 US ACGIH Threshold Lim		desiana				
n-Hexane (CAS 110-54 US ACGIH Threshold Lim n-Hexane (CAS 110-54	it Values: Skin	designa	tion	be absorbed th	rough the skin	

Product name: Camie 365 Hibond Adhesive LT

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Provide eyewash station.
Individual protection measures	, such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear protective gloves.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Color	Not available.
Form	Aerosol.
Physical state	Gas.
Flash point	-156.00 °F (-104.44 °C) estimated
Melting point/freezing point	Not available.
Odor	Not available.
рН	Not available.
Solubility(ies)	Not available.
Vapor density	Not available.
Vapor pressure	47.1 psig @70F estimated
Viscosity	Not available.
Other information	
Specific gravity	0.782 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia. However, ingestion is not likely to be a primary route of occupational exposure.
Inhalation	No adverse effects due to inhalation are expected.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause central nervous system effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Information on toxicological eff	ects

Acute toxicity

Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product	Species	Test Results
Camie 365 Hibond Adhesive L	Г (CAS Mixture)	
Acute		
<i>Dermal</i> LD50	Rabbit	104 4386 ml/kg. ostimatod
LD50		104.4386 ml/kg, estimated
	Rat	18075.8809 mg/kg, estimated
Inhalation		
LC50	Mouse	2349.6196 mg/l, 15 Minutes, estimated
		1834.3156 mg/l, 30 Minutes, estimated
	Rat	10432.7334 mg/l, 15 Minutes, estimated
		1466.2548 mg/l, 4 Hours, estimated
		1119.4457 mg/l/4h, estimated
		261.6188 mg/l, 8 Hours, estimated
Oral		
LD50	Mouse	15665.7959 mg/kg, estimated
	Rabbit	27885.1172 mg/kg, estimated
	Rat	174.1027 mg/kg, estimated
Other		
LD50	Mouse	6772.8462 mg/kg, estimated
LDOO	Rat	28720.627 mg/kg, estimated
0		
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal LD50	Rabbit	20000 mg/kg
LD50	Rabbit	
		20 ml/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours
		50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Other		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg
Dimethyl Ether (CAS 115-10-6)		
Acute		
Inhalation		
LC50	Mouse	494.36 mg/l, 15 Minutes
		385.94 mg/l, 30 Minutes
	Rat	308.5 mg/l, 4 Hours
n-Hexane (CAS 110-54-3)		
Acute		
Inhalation		
LC50	Mouse	48000 mg/l, 4 Hours
Oral	mouoo	
LD50	Rat	24 mg/kg
	Wistar rat	
	vvisiai iäl	49 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation	Det	
LC50	Rat	> 1442.847 mg/l, 15 Minutes

Components	Species		Test Results	
			658 mg/l/4h	
Skin corrosion/irritation	Causes skir			
Serious eye damage/eye irritation	Causes serious eye irritation.			
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	This produc	t is not expected to cause skin sensitiza	tion.	
Germ cell mutagenicity		No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This produc	t is not considered to be a carcinogen b	y IARC, ACGIH, NTP, or OSHA.	
Reproductive toxicity	Suspected of	of damaging fertility or the unborn child.		
Specific target organ toxicity - single exposure	Narcotic effe	Narcotic effects.		
Specific target organ toxicity - repeated exposure	May cause	May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard	May be fata	l if swallowed and enters airways.		
12. Ecological information	n			
Ecotoxicity	Harmful to a	equatic life with long lasting effects.		
Product		Species	Test Results	
Camie 365 Hibond Adhesive	LT (CAS Mixtu	ıre)		
Crustacea	EC50	Daphnia	678.6467 mg/L, 48 Hours, estimated	
Fish	LC50	Fish	16.1188 mg/L, 96 Hours, estimated	
Components		Species	Test Results	
Acetone (CAS 67-64-1)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	
Persistence and degradability	No data is a	vailable on the degradability of this proc	luct.	
Bioaccumulative potential	No data ava	ilable.		
Partition coefficient n-octar Dimethyl Ether Acetone Propane 3-Methylpentane 2-Methylpentane n-Hexane	nol / water (lo	g Kow) 0.1 -0.24 2.36 3.6 3.74 3.9		
Mobility in soil	No data available.			
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
13. Disposal consideratio	ns			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.			
Local disposal regulations	Dispose in a	accordance with all applicable regulation	IS.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.			
US RCRA Hazardous Waste	e U List: Refei	rence		
Acetone (CAS 67-64-1)		U002		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.			
14. Transport information	I			
DOT				
UN number	UN1950			
UN proper shipping pame	Aorocola fla	mmable		

Aerosols, flammable

UN proper shipping name

Transport hazard class(es)	2.1
Subsidiary class(es)	Not available.
Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Labels required	None
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	2.1
	Subsidiary class(es)	-
	Packaging group	Not available.
	Environmental hazards	No
	Labels required	2.1
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Packaging Exceptions	LTD QTY
IME)G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	2.1
	Subsidiary class(es)	-
	Packaging group	Not available.
	Environmental hazards	
	Marine pollutant	No
	Labels required	None
	EmS	Not available.
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Packaging Exceptions	LTD QTY
	nsport in bulk according to nex II of MARPOL 73/78 and	Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code DOT





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export	Notification (40 CFR 707. Su	bpt. D)	
Not regulated.	-	. ,	
CERCLA Hazardous Substa	nce List (40 CFR 302.4)		
Acetone (CAS 67-64-1)		LISTED	
n-Hexane (CAS 110-54-3			
US. OSHA Specifically Regu	liated Substances (29 CFR 1	1910.1001-1050)	
Not listed. SARA 304 Emergency relea	se notification		
Not regulated.			
Superfund Amendments and Re	authorization Act of 1986 (S		
Hazard categories	Immediate Hazard - Yes	, i o o	
	Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No		
SARA 302 Extremely hazardous substance	No		
SARA 311/312 Hazardous chemical	No		
ther federal regulations			
Clean Air Act (CAA) Sectior	112 Hazardous Air Pollutar	its (HAPs) List	
n-Hexane (CAS 110-54-3	·	Provention (40 OFP CO 400)	
Clean Air Act (CAA) Sectior Dimethyl Ether (CAS 115		16venuon (40 CFK 00.130)	
Propane (CAS 74-98-6)			
Safe Drinking Water Act (SDWA)	Not regulated.		
Chemical Code Number	r	sential Chemicals (21 CFR 1310.02(b)	and 1310.04(f)(2) and
Acetone (CAS 67-64		6532 Exampt Chamical Mixtures (24 CEB 4	240 42/0)
Acetone (CAS 67-64		Exempt Chemical Mixtures (21 CFR 1 35 % weight/volumn	310.12(0))
DEA Exempt Chemical			
Acetone (CAS 67-64		6532	
Food and Drug Administration (FDA)	Not regulated.		
IS state regulations			
US. New Jersey Worker and	Community Right-to-Know	Act	
Dimethyl Ether (CAS 115		500 lbs	
n-Hexane (CAS 110-54-3		500 lbs	
Propane (CAS 74-98-6)	andaua Cubatanas-	500 lbs	
US. Pennsylvania RTK - Haz			
2-Methylpentane (CAS 1 3-Methylpentane (CAS 9			
Acetone (CAS 67-64-1) Dimethyl Ether (CAS 115 n-Hexane (CAS 110-54-3	-10-6)		
Propane (CAS 74-98-6)	<i>''</i>		
US. California Proposition 6	5		
	Vater and Toxic Enforcement as carcinogens or reproductiv	Act of 1986 (Proposition 65): This mater /e toxins.	ial is not known to contain an
nternational Inventories			
Country(s) or region	Inventory name		On inventory (yes/no
Australia	Australian Inventory of Cher	nical Substances (AICS)	N
Canada	Domestic Substances List (I	DSL)	١
Canada	Non-Domestic Substances	List (NDSL)	Ν
China	Inventory of Existing Chemi	cal Substances in China (IECSC)	Ν
Europe	European Inventory of Exist Substances (EINECS)	ing Commercial Chemical	Ν
Furana		amiaal Substances (FLINCS)	Ν.

Europe

Japan

European List of Notified Chemical Substances (ELINCS)

Inventory of Existing and New Chemical Substances (ENCS)

No

No

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-17-2014
Revision date	05-12-2014
Version #	03
Further information	Not available.
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Product Codes Composition / Information on Ingredients: Ingredients